




# DE NIRO

NEW-BUILD 90MM LED DOWNLIGHT



- The De Niro range of LED downlights share a uniform bulb and driver set, which twist and click into the different fascia styles.
- Gimbal adjustment feature to suit angled ceilings, and directional lighting applications – 25° Tilt
- IC-4 Rated, can be abutted and covered with approved insulation materials



Code	Type	Power (W)	Lumens Output	Colour Temp (k)	Fascia (mm)	Cutout (mm)	Glare	Trade Price (\$)
NC3	White	8	700	3000	90 Ø	70-80	UGR<22	62.50
NC4	White	8	730	4000	90 Ø	70-80	UGR<22	62.50
NC3S	Silver	8	700	3000	90 Ø	70-80	UGR<22	62.50
NC4S	Sliver	8	730	4000	90 Ø	70-80	UGR<22	62.50
NC3B	Black	8	700	3000	90 Ø	70-80	UGR<22	62.50
NC4B	Black	8	730	4000	90 Ø	70-80	UGR<22	62.50


High Output units can be made available on request  
Made to order locally, short delays may occur





# DE NIRO

RETROFIT 110MM LED DOWNLIGHT



- The De Niro range of LED downlights share a uniform bulb and driver set, which twist and click into the different fascia styles.
- Gimbal adjustment feature to suit angled ceilings, and directional lighting applications – 25° Tilt
- IC-4 Rated, can be abutted and covered with approved insulation materials



Code	Type	Power (W)	Lumens Output	Colour Temp (k)	Fascia (mm)	Cutout (mm)	Glare	Trade Price (\$)
NR3	Retro White	8	700	3000	110 Ø	70-92	UGR<22	64.20
NR4	Retro White	8	730	4000	110 Ø	70-92	UGR<22	64.20
NR3S*	Retro Silver	8	700	3000	110 Ø	70-92	UGR<22	P.O.A
NR4S*	Retro Silver	8	730	4000	110 Ø	70-92	UGR<22	P.O.A
NR3B*	Retro Black	8	700	3000	110 Ø	70-92	UGR<22	P.O.A
NR4B*	Retro Black	8	730	4000	110 Ø	70-92	UGR<22	P.O.A


High Output units can be made available on request  
Made to order locally, short delays may occur

\*Black and Silver available on request MOQs apply



# DE NIRO

SQUARE LED DOWNLIGHT



- The De Niro range of LED downlights share a uniform bulb and driver set, which twist and click into the different fascia styles.
- Gimbal adjustment feature to suit angled ceilings, and directional lighting applications – 25° Tilt
- IC-4 Rated, can be abutted and covered with approved insulation materials



Code	Type	Power (W)	Lumens Output	Colour Temp (k)	Fascia (mm)	Cutout (mm)	Glare	Trade Price (\$)
NSQ3	Square White	8	700	3000	110 SQ	70-92	UGR<22	66.70
NSQ4	Square White	8	730	4000	110 SQ	70-92	UGR<22	66.70
NSQ3S*	Square Silver	8	700	3000	110 SQ	70-92	UGR<22	P.O.A
NSQ4S*	Square Silver	8	730	4000	110 SQ	70-92	UGR<22	P.O.A
NSQ3B*	Square Black	8	700	3000	110 SQ	70-92	UGR<22	P.O.A
NSQ4B*	Square Black	8	730	4000	110 SQ	70-92	UGR<22	P.O.A

High Output units can be made available on request  
Made to order locally, short delays may occur


\*Black and Silver available on request MOQs apply





# DE NIRO

LOW GLARE LED DOWNLIGHT



- The De Niro range of LED downlights share a uniform bulb and driver set, which twist and click into the different fascia styles.
- Low Glare option in the De Niro Range
- IC-4 Rated, can be abutted and covered with approved insulation materials



Code	Type	Power (W)	Lumens Output	Colour Temp (k)	Fascia (mm)	Cutout (mm)	Glare	Trade Price (\$)
NLG3	Low Glare White	8	700	3000	110 Ø	70-92	UGR<19	83.35
NLG4	Low Glare White	8	730	4000	110 Ø	70-92	UGR<19	83.35
NLG3S*	Low Glare Silver	8	700	3000	110 Ø	70-92	UGR<19	P.O.A
NLG4S*	Low Glare Silver	8	730	4000	110 Ø	70-92	UGR<19	P.O.A
NLG3B*	Low Glare Black	8	700	3000	110 Ø	70-92	UGR<19	P.O.A
NLG4B*	Low Glare Black	8	730	4000	110 Ø	70-92	UGR<19	P.O.A

High Output units can be made available on request  
Made to order locally, short delays may occur

\*Black and Silver available on request MOQs apply